



ADJUST-A-BODY WITH CONCRETE ANCHOR BOLT

CABLE DIA.	PART NO.	USE WITH FERRULE NO.	"L" OPEN	"L" CLOSED	"S" THREAD	"T" THREAD	"LS"	"LT"	"LOQ"	"LN"	"LR"	"D"	CONCRETE ANCHOR - CARBON STEEL	CONCRETE ANCHOR - STAINLESS STEEL
1/8"	A-JAB4	F-4	4 1/2"	3 1/8"	3/8-16	5/16-24 LH	.5"	2.313"	3.188"	.375"	2.75"	.49"	RM-38	SRM-38
3/16"	A-JAB6	F-6		3 1/2"	1 1/2-13	7/16-20 LH	1.125"	2.5"	3.938"	.5"	3"	.617"	RM-12	SRM-12

*USE WITH "RED HEAD" BRAND CONCRETE ANCHOR

THE CABLE CONNECTION
 52 HEPNER DR.
 CARSON CITY, NV 89706
 TOLL FREE: 1-800-851-2961
 PHONE: (775) 885-1443
 FAX: (775) 885-2734
 www.ultra-tec.com

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS, AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
3. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.

MATERIAL:	316 SS	
PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF THE CABLE CONNECTION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF THE CABLE CONNECTION IS PROHIBITED.		
CABLE RAILING HARDWARE SIZE DWG. NO. A SPEC SHEET REV.		DO NOT SCALE DRAWING SHEET 1 OF 1